



NOTES

- 1- K-KILO-1000 MEG-1,000,000 F-FARAD H-HENRY W-WATT
- 2- M-MILLI-0.001 S-SECOND U-MICRO-0.000001
- 3- UNLESS OTHERWISE INDICATED IN OHMS 1/2 WATT
- 4- ALL CAPACITANCE VALUES ARE IN UUF
- 5- ALL INDUCTANCE VALUES ARE IN UH
- 6- 3-DIRECTIONAL INDICATOR INDICATES CLOCKWISE ROTATION, UNLESS FROM SHAFT (KNOB) END
- 7- CR 705, 6, 7, 8, 10 DESIGNATES A SERIES STRING OF 18 SILICON DIODES, EACH (GROUP) OF THREE DIODES IS SHUNTED BY A CAPACITOR
- 8- L701, 702, 703 ARE IN SAME CAN WITH 705
- 9- TB 82 NOT INCLUDED ON EARLY UNITS
- 10- TRANSFORMER SHOWN STRAPPED FOR 230V A.C. 4 300V D.C. OTHER COMBINATIONS STENCILED ON TRANSFORMER
- 11- THESE DIMENSIONS ARE PROVIDED TO ACCOMMODATE REMOTE CONTROL DEVICES. DIMENSIONS FOR REMOTE CONTROL DEVICES ARE NOT SHOWN. DIMENSIONS FOR REMOTE CONTROL DEVICES ARE SHOWN IN SEPARATE CONTROL PANEL DRAWING FOR EXACT CONNECTIONS

PRELIMINARY

DATE	BY	REVISION	DESCRIPTION
1947	...	1	...
1947	...	2	...
1947	...	3	...
1947	...	4	...
1947	...	5	...
1947	...	6	...
1947	...	7	...
1947	...	8	...
1947	...	9	...
1947	...	10	...

STANDARD ELECTRONICS
 1400 UNIVERSITY AVENUE
 ANN ARBOR, MICHIGAN
 SCHEMATIC DIAGRAM
 E-3000-1-101