



D/A SEQUENCE TABLE T.P.104 V

STEP	Q0	Q1	Q2	Q3	A,88C	60D
0	L	L	L	L	2.77	4.77
1	H	L	L	L	2.87	4.87
2	L	H	L	L	2.97	4.97
3	H	H	L	L	3.07	5.07
4	L	L	H	L	3.17	5.17
5	H	L	H	L	3.27	5.27
6	L	H	H	L	3.37	5.37
7	H	H	H	L	3.47	5.47
8	L	L	L	H	3.57	5.57
9	H	L	L	H	3.67	5.67
10	L	H	L	H	3.77	5.77
11	H	H	L	H	3.87	5.87
12	L	L	H	H	3.97	5.97
13	H	L	H	H	4.07	6.07
14	L	H	H	H	4.17	6.17
15	H	H	H	H	4.27	6.27

4. 7815 SELECTED FOR 15±.05V
 3. () = "D" VERSION VALUES
 2. — = FEMALE/T.B.
 — = MALE
 — = 1N4002
 — = 1N34A
 — = 1N4148/914
 — = 1N749A/1N5229B
 1. ALL VALUES:
 A. MULTIPLIER AT DECIMAL LOCATION, i.e.
 3.6kΩ = 3x10³, 0.047μF = 4.7x10⁻², 22μF = 22x10⁻⁶
 B. p=10⁻¹², n=10⁻⁹, μ=10⁻⁶, m=10⁻³, k=10³, M=10⁶, G=10⁹
NOTES: UNLESS OTHERWISE SPECIFIED

APPROVALS	DATE	dorrough	
DRAWN E.A.		CHECKED	DESCRIPTION
ENGR. KG		APP'D. M.D.	PEAK HOLD; LOUDNESS MONITORS
MATL. N/A		MODEL-P/N	MODELS 40A-C, 60D40
FINISH		SIZE	REV F
		SCALE	STATE OF DWG FINAL
			SHEET 2 OF 2